



## Light Run Time (in Hours)



4000 Lumen  
2 Light Heads



9500 Lumen  
2 Light Heads



9800 Lumen  
2 Light Heads

Air-Light®



22 Amp Battery

Air-Light® II



35 Amp Battery

1 Head Operating

14+

2 Heads Operating

7+

Run Hours

Configuration  
not offered

1 Head Operating

7+

2 Heads Operating

4+

Run Hours

1 Head Operating

25+

2 Heads Operating

14+

1 Head Operating

9+

2 Heads Operating

5+

1 Head Operating

9+

2 Heads Operating

5+

### Light Head Specifications:

- IP-68 rated dustproof and waterproof
- 60° wide flood beam pattern
- Anodized aluminum frame with a polycarbonate lens
- Operating temperature: -40°F to 176°F (-40°C to 80°C)
- Lifetime warranty on light heads



## Emergency Response Ventilation Kits

DC Powered Ventilation and portable area lighting in one kit!

### Emergency Response Ventilation Kits

Item No.	Description
ERVK-15DC	CVF-15DCAN Canister Fan and AL2-4K-35 Light
ERVK-25DC	CVF-25DCAN Canister Fan and AL2-4K-35 Light

Fan Details on Page 69 and Air-Light® details on page 82.

### Emergency Response Ventilation Kit ERVK-15DC

