

10" In-Line Steel Axial Fans



SVF-10E
C_{US} CE

10" to 8" Duct Adapters
Supplied for Intake and Exhaust



SVF-10EXP
C_{US} CE

Dual Grounding Lugs to
Remove Static Electricity

Standard Models	Model No.	Free Air	25' 1-90° Bend	25' 2-90° Bends
10" Blower (60 Hz)	SVF-10E	868 CFM	648 CFM	589 CFM
10" Blower (50 Hz)	SVF-10AC50	723 CFM	540 CFM	491 CFM
Explosion-Proof Models	Model No.	Free Air	25' 1-90° Bend	25' 2-90° Bends
10" EXP Blower (60 Hz)	SVF-10EXP	994 CFM	738 CFM	678 CFM
10" EXP Blower (50 Hz)	SVF-10X220	828 CFM	615 CFM	565 CFM

The 10" in-line axial fan is designed as a stand alone fan or can be attached in series to run long lengths of ventilation duct. Intake and exhaust flanges allow for either 8" or 10" duct to be attached to either end of the blower to achieve positive or negative ventilation. Made of lightweight steel, the blower is available in standard or explosion-proof electric versions.

Fans Approved for Hazardous Locations:

SVF-10EXP - CSA C/US certified for Classes I and II, Groups C, D, E, F, and G.

SVF-10X220 - ATEX and IECEx certified for II 2 Gc Ex d IIB T6 Gb

10" In-Line Steel Axial Fans

Item No.	Description
	Non-Hazardous Locations
SVF-10E	10" Electric in-line fan, continuous duty, 1/3 HP, 115 VAC, 60 Hz. CSA C/US Certified. CE Registered. 30 lbs.
SVF-10AC50	10" Electric in-line fan, continuous duty, 1/3 HP, 230 VAC, 50 Hz. CE Registered. 30 lbs.
	Hazardous Locations
SVF-10EXP	10" Explosion-proof electric in-line fan, continuous duty, 1/3 HP, 115 VAC, 1-phase, 60 Hz. CSA C/US Certified. CE Registered. 38 lbs. Plug sold separately.
SVF-10X220	10" Explosion-proof electric in-line fan, continuous duty, 1/3 HP, 230 VAC, 50/60 Hz. ATEX and IECEx certified. 38 lbs. Plug sold separately.



For Use In
Hazardous
Locations

Explosion-Proof plug sold separately. No additional charge for installation prior to shipment.

Explosion-Proof Plugs

Item No.	Description
ELAP15231	15 AMP, 125 VAC, EXP plug w/quick wiring (5-15P) USA / Canada
ELAP20231	20 AMP, 125 VAC, EXP plug w/quick wiring (5-20P) USA / Canada
ELAP15232	15 AMP, 250 VAC, EXP plug w/quick wiring (6-15P) International
ELAP20232	20 AMP, 250 VAC, EXP plug w/quick wiring (6-20P) International

No additional charge for installation prior to shipment.

Explosion-Proof Plugs



ELAP15231



ELAP20231



ELAP15232



ELAP20232

